

6 位數微電腦型盤面式電錶(Low Power)(24X48mm)

(6 DIGITAL MICROPROCESS PANEL METER,(Low Power)24x48mm)

MODEL
MMS-6



RoHS

■特點(FEATURES)

- 精確度0.015%滿刻度±3位數(Accuracy 0.015% F.S.±3digit)
- 可量測直流電壓/直流電流/電位計...等信號
(Measuring DCA/DCV/Potentiometer...)
- 顯示範圍-999999~999999可任意規劃(Programmable rate -999999 to 999999 digit)
- 小數點可任意規劃(Decimal point can be modified)
- 尺寸小,穩定性高(Dimension small and High stability)
- CE認證(CE EMC certification)

1.MODEL:MMS-6

(選購型號)

NO	Input Type	NO	DCV	NO	DCV	NO	DCA	NO	Potentiometer	NO	Aux.Power
A	DC	11	0~±50mV	16	0~±100V	24	0~±20mA	33	0~100%	A	DC5V(Isolating)
D	Potentiometer	12	0~±5V	17	0~±600V	25	0~±1A	39	SPECIFIED	B	DC12V(Isolating)
		13	0~±10V	19	SPECIFIED	26	0~±5A		•Three wire connection •Exciting voltage DC3.3V(<15mA)	C	AC/DC20~260V(Isolating)
		15	0~±50V			29	SPECIFIED				•LESS ±10% for DC Input •LESS 1VA for Input

2.SPECIFICATION (主要規格)

- Measuring accuracy : 0.015% F.S.±3 digit
(精確度) (23±5°C)
- Sampling time : 20 cycles/sec.
(取樣時間)
- Display average times : 1~99 times adjustable
(顯示值平均次數)
- Readout range : -999999~999999 digit adjustable
(顯示值範圍)
- Zero (offset) range : -999~999 digit adjustable
(歸零調整範圍)
- Span (scale) range : -999~999 digit adjustable
(最大值調整範圍)
- Over input indication : " doFL " or "-doFL"
(過載顯示)
- Polarity display : When input is negative " POL " display
(極性顯示)
- Display : Red high efficiency LEDs high 7.68mm(0.3")
(顯示幕)
- Temp. coefficient : 20ppm/°C (0~50°C)
(溫度係數)
- Parameter setting : Touch switches
(參數設定方式)
- Memory mode : Non-volatile E² PROM memory
(記憶型式)
- Dielectric strength : 1KVac/1 min. (input/power)
(絕緣耐壓能力)
- Operating condition : 0~50°C (20 to 90% RH non-condensed)
(使用環境條件)
- Storage condition : 0~70°C (20 to 90% RH non-condensed)
(存放環境條件)
- Outside dimension : 24x48x48.5mm
(外型尺寸)
- Case material : ABS
(外殼材料)
- CE EMC Certification : EN 55022:1998/A1:2000 Class A
EN 61000-3-2:2000
EN 61000-3-3:1995/A1:2001
EN 55024:1998/A1:2001
(CE認證)

3.OUTSIDE DIMENSION AND CONNECTION DIAGRAM (外型尺寸與開孔尺寸與配線圖)

